

**MONTANA BOARD OF OIL AND GAS CONSERVATION**  
2535 ST. JOHNS AVENUE, BILLINGS, MONTANA 59102

Lease Name:  
Piano Man 7-6-31

Lease Type (Private/State/Federal):  
Private

Application for Permit To:

Drill  Deepen  Re-enter   
Oil  Gas  Other

Well Number:  
#4H

Operator: Kraken Operating LLC  
Address: 9805 Katy Freeway Suite 300  
City: Houston State: TX Zip: 77024  
Telephone Number: 713-360-7705

Field Name or Wildcat:  
Wildcat **RECEIVED**  
Unit Name (if applicable):  
N/A **SEP 05 2023**

Surface Location of Well (quarter-quarter and footage measurements):  
NWNE Section 18, T25N, R58E - 1285' FNL & 2418' FEL

Objective Formation(s):  
Middle Bakken **MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS**

Proposed Total Depth and Bottom-hole Location(s) if directional or horizontal well:  
TD 26,448' MD, 10,499' TVD  
NENE Section 31, T26N, R58E - 205' FNL & 608' FEL

Township, Range, and Section:  
Sec 18 T25N R58E

County:  
Richland County, MT

Elevation (indicate GL or KB):  
2364' GL

Size and description of drilling/spacing unit and applicable order, if any:	Formation at total depth:	Anticipated Spud Date:
1908(S-7,6,T25N-R58E,S-31,T26N-R58E)49-2023 & 50-2023	Middle Bakken	3/2/2024

Hole Size	Casing Size	Weight / Foot	Grade (API)	Depth	Sacks of Cement	Type of Cement
12 1/4	9 5/8	36#	J-55	2090	467	See Attached
8 3/4	7	32#	P-110	11001	654	See Attached
6	4 1/2	13.5#	P-110	26448	802	See Attached

Describe Proposed Operations:  
Describe or attach labeled diagram of blowout preventer equipment. Indicate if air drilled or describe mud program.  
See attachments for details

Kraken Operating, LLC requests variance to not run open hole logs on the subject well. Offset logs can be found for the Kittleson 24-8TFH (API#: 25-083-22933), SHL: 405' FSL & 1937' FWL SESW Sec. 08 T25N R58E.

**BOARD USE ONLY**

Approved (date) NOV 02 2023 Permit Fee \$15000  
By Benjamin J Davis Check Number 4195  
Title Technical Program Coordinator Permit Expire MAY 02 2024  
Permit Number 32888

THIS PERMIT IS SUBJECT TO THE CONDITIONS OF APPROVAL STATED ON THE BACK

API Number: 25 - 083 - 23462

The undersigned hereby certifies that the information contained on this application is true and correct:

Signed (Agent) Matt Dan  
Title Senior Regulatory Analyst  
Date 8/22/2023  
Telephone Number 713-360-7705

Samples Required: NONE  ALL \_\_\_\_\_ FROM \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Core chips to address below, full cores to USGS, Core Laboratory, Arvada, CO. Required samples must be washed, dried and delivered prepaid to:

Montana Board of Oil and Gas Conservation  
2535 St. Johns Avenue  
Billings, MT 59102

## SUPPLEMENTAL INFORMATION

Note: Additional information or attachments may be required by Rule or by special request.

1. Attach a survey plat certified by a registered surveyor. The survey plat must show the location of the well with reference to the nearest lines of an established public survey.
2. Attach an 8 1/2 x 11" photocopy of that portion of a topographic map showing the well location, the access route from county or other established roads, residences, and water wells within a 1/2 mile radius of the well.
3. Attach a sketch of the well site showing the dimensions and orientation of the site, the size and location of pits, topsoil stockpile, and the estimated cut/fill at the corners and centerstake. (Note: the diagram need not be done by an engineer or surveyor). Attach a sketch of a top view and two side views of the reserve pit(s), if utilized. The reserve pit sketch must show the length, width, depth, cut and fill, amount of freeboard, area of topsoil stockpile, and the height and width of berms.
4. Describe the type and amount of material or liner, if any, to be used to seal the reserve pit. If a synthetic liner is used, indicate the liner thickness (mils), bursting strength, tensile strength, tear strength, puncture resistance, hydrostatic resistance, or attach the manufacturer's specifications.
5. Describe the proposed plan for the treatment and/or the disposal of reserve pit fluids and solids after the well is drilled. If the operator intends to dispose of or treat the reserve pit contents off-site, specify the location and the method of waste treatment and disposal. (Note: The operator must comply with all applicable federal, state, county, and local laws and regulations with regard to the handling, transportation, treatment, and disposal of solid wastes.)
6. Does construction of the access road or location, or some other aspect of the drilling operation require additional federal, state, or local permits or authorizations? If yes, indicate the type of permit or authorization required:
  - No additional permits needed
  - Stream crossing permit (apply through county conservation district)
  - Air quality permit (apply through Montana Department of Environmental Quality)
  - Water discharge permit (apply through Montana Department of Environmental Quality)
  - Water use permit (apply through Montana Department of Natural Resources and Conservation)
  - Solid waste disposal permit (apply through Montana Department of Environmental Quality)
  - State lands drilling authorization (apply through Montana Department of Natural Resources and Conservation)
  - Federal drilling permit (specify agency)
  - Other federal, state, county, or local permit or authorization: (specify type) \_\_\_\_\_

### NOTICES:

1. Date and time of spudding must be reported to the Board verbally or in writing within 72 hours after the commencement of drilling operations.
2. The operator must give notice of drilling operations to the surface owner as required by Section 82-10-503, MCA, before the commencement of any surface activity.

### BOARD USE ONLY

### CONDITIONS OF APPROVAL

The operator must comply with the following condition(s) of approval:

SEE  
ATTACHED  
CONDITIONS OF APPROVAL

RECEIVED  
SEP 05 2023

**WARNING: Failure to comply with conditions of approval may void this permit.**

MONTANA BOARD OF OIL &  
GAS CONSERVATION • BILLINGS

**Kraken Operating, LLC Proposed Well Stimulation**

Total Clean Fluid – 235,000 bbls

Maximum Anticipated Treating Pressure – 9,800 psi

**Hydraulic Fracturing Fluid Components Information Disclosure:**

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Mass per Component (LBS)	Maximum Ingredient Concentration in HF Fluid (% by mass)**
Water	Operator	Carrier	Carrier	7732-18-5	100.00%	82,315,800.00	84.06572%
Surf-Flo 430	Innospec	Flowback Additive	MSDS and Non-MSDS Ingredients Listed Below			7,435.80	0.00759%
FRP-1S	Liberty Oilfield Services	Friction reducer	MSDS and Non-MSDS Ingredients Listed Below			252,853.79	0.25823%
DVA-75	Liberty Oilfield Services	Diverting Agent	MSDS and Non-MSDS Ingredients Listed Below			469.00	0.00048%
Blocker 5000	Lubrizol	Biocide	MSDS and Non-MSDS Ingredients Listed Below			8,387.32	0.00857%
ScaleCease 7103	Innospec	Scale Inhibitor	MSDS and Non-MSDS Ingredients Listed Below			15,850.17	0.01619%
HCL-15	Liberty Oilfield Services	Solvent	MSDS and Non-MSDS Ingredients Listed Below			17,295.26	0.01766%
ACL-300	WST	Corrosion Inhibitor	MSDS and Non-MSDS Ingredients Listed Below			67.43	0.00007%
WA-100	WST	Wetting Agent	MSDS and Non-MSDS Ingredients Listed Below			34.79	0.00004%
IC-50S	WST	Iron Control	MSDS and Non-MSDS Ingredients Listed Below			125.74	0.00013%
Liberty Clean Out	Liberty Oilfield Services	Cleanup Solution	MSDS and Non-MSDS Ingredients Listed Below			74.86	0.00008%
Crystalline Silica	Liberty Oilfield Services	Sand	MSDS and Non-MSDS Ingredients Listed Below			15,300,000.00	15.62520%
The trade name(s) of the additive(s) used, supplier(s), and the purpose(s) of the additive(s) are listed below. The ingredient(s) for the above additive(s) are listed below.							
	Liberty Oilfield Services	Sand	Crystalline Silica (quartz)	14808-60-7	99.90%	15,284,700.00	15.60963%
	Liberty Oilfield Services	Sand	Aluminum Oxide	1344-28-1	1.00%	153,000.00	0.15625%
	Liberty Oilfield Services	Friction reducer	Petroleum distillates, hydrotreated light	64742-47-8	45.00%	113,784.20	0.11620%
	Liberty Oilfield Services	Sand	Iron Oxide	1309-37-1	0.10%	15,300.00	0.01563%
	Liberty Oilfield Services	Sand	Titanium Oxide	13463-67-7	0.10%	15,300.00	0.01563%
	Innospec	Scale Inhibitor	Water	7732-18-5	95.00%	15,057.66	0.01538%
	Liberty Oilfield Services	Solvent	Water	7732-18-5	85.00%	14,700.97	0.01501%
	Liberty Oilfield Services	Friction reducer	Poly(oxy-1,2-ethanediy), a-trifluoro-hydroxy-, branched	69011-36-5	3.00%	7,585.61	0.00775%
	Innospec	Flowback Additive	Water	7732-18-5	95.00%	7,064.01	0.00721%
	Liberty Oilfield Services	Solvent	Hydrochloric Acid	7647-01-0	15.00%	2,394.29	0.00265%
	Lubrizol	Biocide	2,2-dibromo-3-nitropropionamide	10222-01-2	10.00%	838.73	0.00086%
	Innospec	Scale Inhibitor	BHMT Phosphonate	Proprietary	5.00%	792.51	0.00081%
	Innospec	Scale Inhibitor	Proprietary Ingredient	Proprietary	5.00%	792.51	0.00081%
	Innospec	Flowback Additive	Benzene sulfonic Acid, dodecyl-empd, with 2-aminomethanol	26836-07-7	10.00%	743.58	0.00076%
	Liberty Oilfield Services	Diverting Agent	Dodecylbenzene sulfonate, triethanolamine salt	37323-41-7	10.00%	743.58	0.00076%
	Innospec	Flowback Additive	Polyacetic Resin	9051-89-2	100.00%	469.00	0.00048%
	WST	Iron Control	Sodium Alpha Olefin Sulfonate	68439-57-6	60.00%	371.79	0.00038%
	Liberty Oilfield Services	Cleanup Solution	2-hydroxypropane-1,2,3-tricarboxylic acid	77-92-9	5.00%	75.45	0.00008%
	WST	Wetting Agent	Oxysucinate and paraffinic stream	876065-86-0	99.00%	74.11	0.00008%
	WST	Corrosion Inhibitor	Ethoxylated Decyl Alcohol	78330-20-8	40.00%	13.92	0.00015%
	Liberty Oilfield Services	Cleanup Solution	2-Propyl-1-ol compound with methylloxurane	38172-91-7	15.00%	10.11	0.00001%
	Innospec	Flowback Additive	C.I. Solvent Yellow 33	8003-22-3	1.00%	0.75	0.00000%
	Innospec	Flowback Additive	Triethanolamine	103-71-6	0.01%	0.67	0.00000%
	Innospec	Flowback Additive	Triethanolamine	141-43-5	0.01%	0.67	0.00000%

**RECEIVED**

SEP 05 2023