

FORM NO. 22 R 10/09 SUBMIT IN QUADRUPPLICATE TO: ARM 36.22.307
ARM 36.22.601

MONTANA BOARD OF OIL AND GAS CONSERVATION
2535 ST. JOHNS AVENUE, BILLINGS, MONTANA 59102

Lease Name: **Mayson Phoenix 17-20**

Lease Type (Private/State/Federal): **Private**

Application for Permit To:

Drill Deepen Re-enter
Oil Gas Other

Well Number: **#1H**

Operator: **Kraken Operating, LLC**
Address: **9821 Katy Freeway, Suite 460**
City: **Houston** State: **TX** Zip: **77024**
Telephone Number: **713-360-7705**

Field Name or Wildcat: **Wildcat**

Unit Name (if applicable): **N/A**

Surface Location of Well (quarter-quarter and footage measurements):
377' FSL & 417' FEL of SESE Sec. 7-T25N-R59E

Objective Formation(s): **Bakken**

Proposed Total Depth and Bottom-hole Location(s) if directional or horizontal well:
TD: **20,757' MD, 10,290' TVD**
BHL: **205' FSL & 540' FWL SWSW Sec 20-T25N-R59E**

Township, Range, and Section: **T25N, R59E, Section 7**

County: **Richland**

Elevation (indicate GL or KB):
GL: **2,028'**

Size and description of drilling/spacing unit and applicable order, if any: **1280 acres (Sections 17 & 20, T25N-R59E) Order: 363-2011**

Formation at total depth: **Bakken**

Anticipated Spud Date: **3/15/2018**

RECEIVED

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION - BILLINGS

Hole Size	Casing Size	Weight / Foot	Grade (API)	Depth	Sacks of Cement	Type of Cement
13 1/2	9 5/8	36	J-55	1,800'	588	See Attached
8 3/4	7	32	P-110	10,603'	698	See Attached
6	4 1/2	11.6 & 13.5	P-110	20,757'	566	See Attached

Describe Proposed Operations:
Describe or attach labeled diagram of blowout preventer equipment. Indicate if air drilled or describe mud program.

Kraken Operating, LLC requests variance to not run openhole logs on the Mayson Phoenix 17-20 #1H. Offset logs will be The Doyle H-7 (API#: 25-083-21661), SHL: 1,750' FNL & 900' FEL Sec. 7-T25N-R59E.

BOARD USE ONLY

Approved (date) **MAR 06 2018** Permit Fee **\$150.00**

By *[Signature]* Check Number **23326**

Title *Petroleum Engineer* Permit Expires **SEP 06 2018**

Permit Number **32253**

THIS PERMIT IS SUBJECT TO THE CONDITIONS OF APPROVAL STATED ON THE BACK

API Number: 25 - **083 - 23353**

The undersigned hereby certifies that the information contained on this application is true and correct:

Signed (Agent) *[Signature]*

Title **Sr. Drilling Engineer**

Date **2/22/2018**

Telephone Number **713-494-4049**

Samples Required: NONE ALL _____ FROM _____ feet to _____ feet

Core chips to address below, full cores to USGS, Core Laboratory, Arvada, CO. Required samples must be washed, dried and delivered prepaid to:

Montana Board of Oil and Gas Conservation
2535 St. Johns Avenue
Billings, MT 59102

RECEIVED

SUPPLEMENTAL INFORMATION

FEB 26 2018

Note: Additional information or attachments may be required by Rule or by special request.

MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS

1. Attach a survey plat certified by a registered surveyor. The survey plat must show the location of the well with reference to the nearest lines of an established public survey.
2. Attach an 8 1/2 x 11" photocopy of that portion of a topographic map showing the well location, the access route from county or other established roads, residences, and water wells within a 1/2 mile radius of the well.
3. Attach a sketch of the well site showing the dimensions and orientation of the site, the size and location of pits, topsoil stockpile, and the estimated cut/fill at the corners and centerstake. (Note: the diagram need not be done by an engineer or surveyor). Attach a sketch of a top view and two side views of the reserve pit(s), if utilized. The reserve pit sketch must show the length, width, depth, cut and fill, amount of freeboard, area of topsoil stockpile, and the height and width of berms.
4. Describe the type and amount of material or liner, if any, to be used to seal the reserve pit. If a synthetic liner is used, indicate the liner thickness (mils), bursting strength, tensile strength, tear strength, puncture resistance, hydrostatic resistance, or attach the manufacturer's specifications.
5. Describe the proposed plan for the treatment and/or the disposal of reserve pit fluids and solids after the well is drilled. If the operator intends to dispose of or treat the reserve pit contents off-site, specify the location and the method of waste treatment and disposal. (Note: The operator must comply with all applicable federal, state, county, and local laws and regulations with regard to the handling, transportation, treatment, and disposal of solid wastes.)
6. Does construction of the access road or location, or some other aspect of the drilling operation require additional federal, state, or local permits or authorizations? If yes, indicate the type of permit or authorization required:
 - No additional permits needed
 - 310 Permit (apply through county conservation district)
 - Air quality permit (apply through Montana Department of Environmental Quality)
 - Water discharge permit (apply through Montana Department of Environmental Quality)
 - Water use permit (apply through Montana Department of Natural Resources and Conservation)
 - Solid waste disposal permit (apply through Montana Department of Environmental Quality)
 - State lands drilling authorization (apply through Montana Department of Natural Resources and Conservation)
 - Federal drilling permit (specify agency)
 - Other federal, state, county, or local permit or authorization: (specify type) _____

NOTICES:

1. Date and time of spudding must be reported to the Board verbally or in writing within 72 hours after the commencement of drilling operations.
2. The operator must give notice of drilling operations to the surface owner as required by Section 82-10-503, MCA, before the commencement of any surface activity.

BOARD USE ONLY

CONDITIONS OF APPROVAL

The operator must comply with the following condition(s) of approval:

WARNING: Failure to comply with conditions of approval may void this permit.



Kraken Operating, LLC

9821 Katy Freeway – Ste. 460, Houston, TX 77024

Typical Completion Procedure Bakken or Three Forks

RECEIVED

FEB 26 2018

**MONTANA BOARD OF OIL &
GAS CONSERVATION • BILLINGS**

After Drilling Rig Moves Off Location

1. MIRU wire line, RIH with gauge ring to at least 100 ft beyond liner top, POOH.
2. RIH and set retrievable plug in liner hanger or in completion liner, POOH with wireline. Run CBL-CCL-GR and casing inspection tool from liner top to surface.
3. Pressure test 7" (intermediate) casing and frac valve. Retrieve plug in liner top.
4. MI and fill frac tanks with fresh water to ensure there will be enough water for the designed frac job.
5. MIRU flowback company. Rig flowback iron from wellhead to 4 phase separator to open top tank.
6. MIRU all frac company equipment, wire line, and all ancillary equipment necessary to frac well.
7. Pump frac job as designed. RDMO frac equipment and wire line.
8. MIRU coiled tubing to mill out frac plugs.
9. Begin flowback of well. Once well has cleaned up, direct full well stream to production battery.
10. RDMO flowback equipment and crew.
11. Turn well over to production department.

Note:

If casing inspection log indicates excessive wear in 7" casing or other conditions require a frac string to be run, the CBL-GR-CCL and casing inspection tool will be run and the 7" casing pressure tested to a lower rating. After the frac string is run, a retrievable plug will be set and the frac string tested prior to the frac.



RECEIVED

FEB 26 2018

**MONTANA BOARD OF OIL &
GAS CONSERVATION • BILLINGS**

Kraken Operating, LLC

48 Stage P&P Design

State: *MT*
County: *Roosevelt County*
API#: *TBD*
AFE#: *TBD*

Prepared for: *Matt Bauerschlag*
Prepared by: *Alejandro Haiek*

February 4, 2016

RECEIVED

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION - BILLINGS



Completion Data

Contact Information

Company:	Kraken Operating, LLC
Company Rep.:	Matt Bauerschlag
Billing Address:	9821 Katy Freeway Suite 460 Houston, TX 77024
Sales Engineer:	Alejandro Haiek
Contact Info:	(661) 345-3450

Well Information

Well Name:	48 Stage P&P Design
State:	MT
County:	Roosevelt County
API No.:	TBD
Legal:	S - T - R
Formation:	Middle Bakken

Completion Information

Completion Type:	Plug & Perf
No. Stages:	48
Stimulation Fluid:	XL Borate
BHST:	200 F
AFE No:	TBD

Intermediate Casing

Depth	Size & Weight	Grade	Vol. (bbl)
9,000'	7.0" - 29 lb/ft	P-110	334.3
			0.0
			0.0
			0.0
			0.0

Liner/Production String

Type	Depth	Size & Weight	Grade	Vol. (bbl)
Liner Top	9,000'			139.9
Liner	20,000'	4.5" - 11.6 lb/ft	P-110	
Frac String	9,000'	4.5" - 11.6 lb/ft	L-80	

Stage Intervals

Stage #	Top	Btm	Vol. (bbl)
Stage 1	19,700'	19,875'	307.5
Stage 2	19,500'	19,675'	304.4
Stage 3	19,300'	19,475'	301.3
Stage 4	19,100'	19,275'	298.2
Stage 5	18,900'	19,075'	295.1
Stage 6	18,700'	18,875'	292.0
Stage 7	18,500'	18,675'	288.8
Stage 8	18,300'	18,475'	285.7
Stage 9	18,100'	18,275'	282.6
Stage 10	17,900'	18,075'	279.5
Stage 11	17,700'	17,875'	276.4
Stage 12	17,500'	17,675'	273.3
Stage 13	17,300'	17,475'	270.2
Stage 14	17,100'	17,275'	267.1
Stage 15	16,900'	17,075'	264.0
Stage 16	16,700'	16,875'	260.9
Stage 17	16,500'	16,675'	257.8
Stage 18	16,300'	16,475'	254.7
Stage 19	16,100'	16,275'	251.6
Stage 20	15,900'	16,075'	248.4
Stage 21	15,700'	15,875'	245.3
Stage 22	15,500'	15,675'	242.2
Stage 23	15,300'	15,475'	239.1
Stage 24	15,100'	15,275'	236.0
Stage 25	14,900'	15,075'	232.9

Stage #	Top	Btm.	Vol. (bbl)
Stage 26	14,700'	14,875'	229.8
Stage 27	14,500'	14,675'	226.7
Stage 28	14,300'	14,475'	223.6
Stage 29	14,100'	14,275'	220.5
Stage 30	13,900'	14,075'	217.4
Stage 31	13,700'	13,875'	214.3
Stage 32	13,500'	13,675'	211.1
Stage 33	13,300'	13,475'	208.0
Stage 34	13,100'	13,275'	204.9
Stage 35	12,900'	13,075'	201.8
Stage 36	12,700'	12,875'	198.7
Stage 37	12,500'	12,675'	195.6
Stage 38	12,300'	12,475'	192.5
Stage 39	12,100'	12,275'	189.4
Stage 40	11,900'	12,075'	186.3
Stage 41	11,700'	11,875'	183.2
Stage 42	11,500'	11,675'	180.1
Stage 43	11,300'	11,475'	177.0
Stage 44	11,100'	11,275'	173.9
Stage 45	10,900'	11,075'	170.7
Stage 46	10,700'	10,875'	167.6
Stage 47	10,500'	10,675'	164.5
Stage 48	10,300'	10,475'	161.4
Stage 49			0.0
Stage 50			0.0

Estimated completions data only.



Operator: Kraken Operating, LLC
 Well Name: 48 Stage P&P Design
 County: Roosevelt County
 API#: TBD

Stimulation Summary

<u>Horsepower Requirements</u>	
Max Pressure:	TBD
Anticipated Treating Pressure:	7,000 psi
Annulus Pressure Required:	TBD
Design Rate:	45 bpm
Min. HHP Required:	7,721 hhp

<u>Fluid Requirements</u>	
Acid Volume:	24,000 gal
Pump Down Volume:	bbl
Total Clean Fluid:	131,314 bbl
Tanks Required:	292

<u>Chemical Requirements</u>			
Gel	83,760 lb	Corr. Inhib.	240 gal
I - XL	4,734 gal	FE Cont.	120 gal
pH	1,578 gal		
FR	429 gal		
Surf.	5,045 gal	Cap AP	1,578 lb
Bio.	1,261 lb	AP	258 lb

<u>Proppant Requirements</u>	
40-70 Mesh White Sand	192,000 lb
30-50 Mesh White Sand	9,808,000 lb

Notes:

RECEIVED

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS



Operator: Kraken Operating, LLC
Well Name: 48 Stage P&P Design
County: Roosevelt County
API#: TBD

Fluid Descriptions

15% HCl		per 1,000 gal
Corrosion Inhibitor		10.0 gal
Iron Control		5.0 gal

SlickRock		per 1,000 gal
Anionic Friction Reducer		0.50 gal
Surfactant		1.00 gal
Dry Biocide (DAZOMET)		0.25 lb

20# Linear		per 1,000 gal
PSG Polymer		20.00 lb
Surfactant		1.00 gal
Dry Biocide (DAZOMET)		0.25 lb
AP Breaker		0.25 lb

20# RockSolid		per 1,000 gal
PSG Polymer		20.00 lb
Instant Borate Crosslinker		1.50 gal
High pH Activator		0.50 gal
Surfactant		1.00 gal
Dry Biocide (DAZOMET)		0.25 lb
Encapsulated AP Breaker		0.50 lb

NOTE: Fluid descriptions are based upon lab results from previous treatments. Actual systems will be determined from lab tests conducted prior to the treatment.

RECEIVED

FEB 26 2018

**MONTANA BOARD OF OIL &
GAS CONSERVATION • BILLINGS**



Operator: Kraken Operating, LLC
 Well Name: 48 Stage P&P Design
 County: Roosevelt County
 API#: TBD

Pump Schedule

Treatment No	Stage Name	Fluid Type	Rate	Fluid Volume	Comm. Fluid Volume	Slurry Volume	Comm. Slurry Volume	Stage Time	Comm. Pump Time	Prop Conc.	Proppant Type	Prop Stage Volume	Comm. Prop Volume
			(bpm)	(gal)	(gal)	(gal)	(mm:ss)	(h:mm:ss)	(ppa)	(lbs)		(lbs)	
1	Injection	SlickRock	12	500	500	500	500	01:00	0:01:00			-	-
	Acid	15% HCl	12	500	1,000	500	1,000	01:00	0:01:59			-	-
	Pad	SlickRock	45	8,000	9,000	8,000	9,000	04:14	0:06:13			-	-
	Scour	20# Linear	45	8,000	17,000	8,181	17,181	04:20	0:10:33	0.50	40-70 Mesh White Sar	4,000	4,000
	Pad	20# Linear	45	13,500	30,500	13,500	30,681	07:09	0:17:41			-	4,000
	1.0 PPA	20# RockSolid	45	9,500	40,000	9,930	40,611	05:15	0:22:57	1.00	30-50 Mesh White Sar	9,500	13,500
	2.0 PPA	20# RockSolid	45	9,500	49,500	10,360	50,971	05:29	0:28:25	2.00	30-50 Mesh White Sar	19,000	32,500
	3.0 PPA	20# RockSolid	45	11,167	60,667	12,683	63,653	06:43	0:35:08	3.00	30-50 Mesh White Sar	33,501	66,001
	4.0 PPA	20# RockSolid	45	25,500	86,167	30,115	93,769	15:56	0:51:04	4.00	30-50 Mesh White Sar	102,000	168,001
	4.0 PPA	20# RockSolid	45	10,083	96,250	11,908	105,676	06:18	0:57:22	4.00	30-50 Mesh White Sar	40,332	208,333
Flush	SlickRock	45	12,915	109,165	12,915	118,591	06:50	1:04:12			-	208,333	
2-48	Pumpdown	SlickRock	12	10,000	5,436,641	10,000	5,879,682	19:50	63:49:44			-	9,791,651
	Acid	15% HCl	12	500	5,437,141	500	5,880,182	01:00	63:50:43			-	9,791,651
	Pad	SlickRock	45	8,000	5,445,141	8,000	5,888,182	04:14	63:54:57			-	9,791,651
	Scour	20# Linear	45	8,000	5,453,141	8,181	5,896,363	04:20	63:59:17	0.50	40-70 Mesh White Sar	4,000	9,795,651
	Pad	20# Linear	45	13,500	5,466,641	13,500	5,909,863	07:09	64:06:25			-	9,795,651
	1.0 PPA	20# RockSolid	45	9,500	5,476,141	9,930	5,919,793	05:15	64:11:41	1.00	30-50 Mesh White Sar	9,500	9,805,151
	2.0 PPA	20# RockSolid	45	9,500	5,485,641	10,360	5,930,153	05:29	64:17:09	2.00	30-50 Mesh White Sar	19,000	9,824,151
	3.0 PPA	20# RockSolid	45	11,167	5,496,808	12,683	5,942,836	06:43	64:23:52	3.00	30-50 Mesh White Sar	33,501	9,857,852
	4.0 PPA	20# RockSolid	45	25,500	5,522,308	30,115	5,972,951	15:56	64:39:48	4.00	30-50 Mesh White Sar	102,000	9,959,652
	4.0 PPA	20# RockSolid	45	10,083	5,532,391	11,908	5,984,859	06:18	64:46:06	4.00	30-50 Mesh White Sar	40,332	9,999,984
Flush	SlickRock	45	6,780	5,539,171	6,780	5,991,638	03:35	64:49:41			-	9,999,984	

Fluid Type	Volume
15% HCl	24,000 gal
SlickRock	1,327,171 gal
20# Linear	1,032,000 gal
20# RockSolid	3,156,000 gal
Total	131,885 bbl

Proppant Type	Total
40-70 Mesh White Sand	192,000 lb
30-50 Mesh White Sand	9,808,000 lb
	lb
	lb
Total	10,000,000 lb

RECEIVED

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS



Operator: Kraken Operating, LLC
 Well Name: 48 Stage P&P Design
 County: Roosevelt County
 AP#: TBD

Additives

Treatment No.	Stage Name	Fluid Type	Fluid Volume (gal)	Gel (ppt)	I - XL (gpt)	pH (gpt)	FR (gpt)	Surf. (gpt)	Bio. (ppt)	Corr. Inhib. (gpt)	FE Cont. (gpt)	Add 9 (gpt)	Add 10 (gpt)	Breaker		
														Cap AP (ppt)	AP (ppt)	
1	Injection	SlickRock	500				0.5	1	0.25							
	Acid	15% HCl	500							10	5					
	Pad	SlickRock	8,000				0.5	1	0.25							
	Scour	20# Linear	8,000	20				1	0.25							0.25
	Pad	20# Linear	13,500	20				1	0.25							0.25
	1.0 PPA	20# RockSolid	9,500	20	1.5	0.5		1	0.25							0.5
	2.0 PPA	20# RockSolid	9,500	20	1.5	0.5		1	0.25							0.5
	3.0 PPA	20# RockSolid	11,167	20	1.5	0.5		1	0.25							0.5
	4.0 PPA	20# RockSolid	25,500	20	1.5	0.5		1	0.25							0.5
	4.0 PPA	20# RockSolid	10,083	20	1.5	0.5		1	0.25							0.5
	Flush	SlickRock	12,915					0.5	1	0.25						
2-48	Pumpdown	SlickRock	10,000													
	Acid	15% HCl	500							10	5					
	Pad	SlickRock	8,000				0.5	1	0.25							
	Scour	20# Linear	8,000	20				1	0.25							0.25
	Pad	20# Linear	13,500	20				1	0.25							0.25
	1.0 PPA	20# RockSolid	9,500	20	1.5	0.5		1	0.25							0.5
	2.0 PPA	20# RockSolid	9,500	20	1.5	0.5		1	0.25							0.5
	3.0 PPA	20# RockSolid	11,167	20	1.5	0.5		1	0.25							0.5
	4.0 PPA	20# RockSolid	25,500	20	1.5	0.5		1	0.25							0.5
	4.0 PPA	20# RockSolid	10,083	20	1.5	0.5		1	0.25							0.5
	Flush	SlickRock	6,780					0.5	1	0.25						

	Gel	I - XL	pH	FR	Surf.	Bio.	Corr. Inhib.	FE Cont.	Add 9	Add 10	Cap AP	AP
	lb	gal	gal	gal	gal	lb	gal	gal	gal	gal	lb	lb
Total	83,760	4,734	1,578	429	5,045	1,261	240	120	-	-	1,578	258

RECEIVED

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS

FEB 26 2018

MONTANA BOARD OF OIL & GAS CONSERVATION • BILLINGS

Hydraulic Fracturing Fluid Product Component Information Disclosure

Standard Kraken Operating, LLC Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**
Water	Operator	Carrier	Water	7732-18-5	100.00000	84.15251
Crystalline Silica, Quartz / Unimin Corp	Frac Vendor	Sand				
Produced Brine Water	Operator	Carrier	Crystalline Silica in the form of Quartz	14808-60-7	98.90000	14.80390
FRP-1S	Frac Vendor	Friction reduction	Produced Brine Water	7732-18-5	100.00000	0.69021
			Petroleum distillates, hydrotreated light	64742-47-8	45.00000	0.03147
			Poly(oxy-1,2-ethanediyl), a-tridecyl-w-hydroxy-, branched	69011-36-5	3.00000	0.00210
HCL-15	Frac Vendor	Solvent	Water	7732-18-5	85.00000	0.01603
			Hydrochloric Acid	7647-01-0	15.00000	0.00283
B-2512WA	Aquaserv	Biocide	Acetone	67-64-1	40.00000	0.00144
			Glutaraldehyde	111-30-8	30.00000	0.00108
			Didecyl dimethyl ammonium	7173-51-5	10.00000	0.00036
			Quaternary ammonium compounds, benzyl-C12-C16-	68424-65-1	5.00000	0.00018
			Ethanol	64-17-5	3.00000	0.00011
SFT-92W	Frac Vendor	Flowback Additive				
			Methanol	67-56-1	30.00000	0.00138
			Benzenesulfonic acid, mono-c10-14-alkyl derivs	68584-22-5	10.00000	0.00046
			Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium	68439-57-6	5.00000	0.00023
			Sodium Hydroxide	1310-73-2	1.00000	0.00005
Liberty Clean Out Fluid	Frac Vendor	Cleanup Solution				
			Naphtha (petroleum) hydrotreated heavy	64742-96-7	100.00000	0.00119
Bioclear 5000	Lubrizol	Biocide				
			2,2-dibromo-3-nitriopropionamide	10222-01-2	10.00000	0.00010
ACI-102HT	WST	Acid Corrosion Inhibitor				
			Ethylene Glycol	107-21-1	40.00000	0.00003
			Water	7732-18-5	25.00000	0.00002
			Dimethyl Formamide	68-12-2	15.00000	0.00001
			Isoquinoline	119-65-3	10.00000	0.00001
			2-Butoxyethanol	111-76-2	5.00000	0.00000

